

Product datasheet

uvex 2 xenova® BOA® 9558 1-3

Perforated safety shoe DIN EN ISO 20345:2022 S1 PL FO SR

Sizes: 35 - 52 | Width: 10, 11, 12



AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole with 15% recycled granulate from residues
- antistatic
- short-term heat resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES

Upper material	• breathable microvelour (clima zone)
Lining material	• suitable for people allergic to chrome
Fastening	• textile distance mesh lining for comfortable foot climate
Reflecting elements	• BOA® Fit System
Comfort	• for increased visibility even in dark working environments
	• soft padding on collar
	• sizes 35-40 have been produced using a women's last
	• dust tongue
Innersole	• removable comfortable innersole

PROTECTIVE FEATURES

Toe cap	• metal-free protective toe cap
Penetration resistance	• metal-free, textile penetration resistance

CERTIFICATES

uvex medicare+	• certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191
100% vegan	• certified free from animal ingredients and products
	• additional protection for people with allergies and intolerances
ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1

SUSTAINABILITY

Recycled/sustainable materials	• midsole, removable innersole, lacing system and heel cap made wholly or partly from recycled materials
	• free from harmful substances in accordance with the uvex restricted substances list

ACCESSORIES/ SPARE PARTS

Replacement innersole	• 9534 7-0
tune-up innersole	• low 95281
	• medium 95282
	• high 95283
BOA® Replacement kit	• 6564000